

Workshop Starter Package Pro



FEATURES

Wheel Balancer

- Single phase 240V Electronic wheel balancer
- Strong and durable cabinet
- Stylish weight tray
- Technologies achieving a zero balance every spin
- Quick release clamping nut
- Accurate to 1g
- Full Alloy programme facility 4 programmes in total
- Bolts securely and safely to any concrete floor
- Bolts securely and safely to any concrete floor
- Automatic data input for wheel diameter and wheel offset on the shaft
- Self calibrating machine (Operator can calibrate periodically making sure of accurate tolerances)
- Set of 4 mounting cones as standard incorporating small four wheel drive cone as standard
- Rear cone mounting spring
- Heavy duty wheel rim width callipers
- Balance weight pliers as standard
- Wheel guard to protect
- Digital Display screen
- Full CE approval
- Motorcycle adaptor (Optional Extra)
- 3,4,5 universal flange plate adaptor (Centre less wheel adaptor) (Optional Extra)
- 24 months warranty*

TECHNICAL DATA

- Max. Wheel Weight - 65 kg
- Balancing Accuracy - +/- 1g
- Rim Diameter - 10" - 24"
- Balancing / Shaft Speed - 200 rpm
- Rim Diameter - 10" - 24"
- Rim Width - 1.5" - 20"
- Measuring Time - 8 secs
- Weight - 122 / 98 kg
- Display Screen - Digital LCD

Workshop Starter Package Pro



FEATURES

Tyre Changer

- Fully integrated power assisted arm for run flat and low profile tyres
- Full jaw inflation (Enables the tyre to be inflated & bead sealed whilst being clamped on the tumtable of the tyre changer) as standard
- Standard – semi professional machine
- Semi automatic with tilting arm (air operated)
- Heavy and durable in construction
- Steel fitting head
- Plastic protection kit supplied as standard (jaw clamping, fitting head insert and bead breaker blade)
- 2500 kg of bead breaker blade
- Heavy duty bead breaker blade
- Strong bead breaker arm
- Fully integrated filter regulator lubricator for quality air supply (ble of the tyre changer) as standard
- Foot pedal operation
- Full length abutment pad for breaking the bead of the tyre
- Integrated tyre inflator
- Heavy duty jaw clamp cylinders
- 240V Electrical supply as standard (3phs optional extra available)
- 24 months warranty

*Terms & conditions apply

TECHNICAL DATA

- Power Supply - 240V (3 Phase available)
- Max. Wheel Diameter - 41"
- Max. Wheel Width - 14"
- Outside clamping - 10" - 21"
- Inside clamping - 12" - 24"
- Air Supply - 8 Bar

Workshop Starter Package Pro



FEATURES

Post Lift

- Dual hydraulic cylinders, direct drive
- Dual point automatic lock release (electromagnetic)
- Two-Stage telescopic lifting arms
- Spiral step-less adjustment arm tray, option extension adapter
- Mechanical safety device, both side manual unlocking, manual drop-down
- Italian made parachute valve under each cylinder in case of hydraulic hose failure
- Relief valve to prevent overloading
- Door opening protection rubber
- Lift height limit safety system
- Synchronization cable
- Aluminum shell motor, 24V low voltage control system
- Emergency manual drop function with adjustable dropping speed
- Machine Welded for extra stability
- 24 months warranty*

*Terms & conditions apply

TECHNICAL DATA

- Capacity – 4000 kg
- Rise Time – 45 secs
- Drop Time - 45 secs
- Lifting Height - 1930mm
- Min. Height - 100mm
- Overall Height - 3724mm
- Overall Width – 3366mm
- Distance Between Columns - 2506mm
- Short Arm Length - 680 - 1020mm
- Long Arm Length - 860 - 1300mm
- Motor Power - 220V / 50Hz / 1 Ph / 3KW

Workshop Starter Package Pro



FEATURES

Compressor

- Automotive duty rated
- Air receivers 2014/29/EU standard
- High efficiency air pumps
- Auto stop / start
- Low vibration levels
- Deep finned cast iron pump
- Thermal protection to all motors
- Spares & service nationwide
- Exports worldwide
- 24 months warranty*

*Terms & conditions apply

TECHNICAL DATA

- Stock Code – CM1112
- Model – EV9/ 100-1
- CFM DISP – 9.0
- LTS DISP – 255
- CFM FAD – 5.1
- LTS FAD – 144
- Stage - 1
- HP - KW – 2.0 - 1.5
- CYL NO – 2
- REC LT – 100
- MAS PSI - 150
- Length – 1010mm
- Width - 370mm
- Height - 750mm
- Weight - 75kg